

WHAT IS CLAIMED IS:

1. An apparatus operable to facilitate add/drop multiplexing of optical signals, the apparatus comprising:

5 an input operable to receive an input optical signal and an added optical signal, and to generate a first and a second copy of the input signal and a first and a second copy of the added signal;

10 a plurality of at least substantially reflective surfaces, each operable to receive either the first signal copies or the second signal copies and to reflect the copies for ultimate combination at an output to form an output signal for transmission, at least one of the at least substantially reflective surfaces comprising a
15 moveable mirror operable to change its position relative to the input to create a phase shift between the first and second signal copies so that either the input optical signal or the added optical signal is communicated as the output signal depending on the position of the at least
20 one moveable mirror.

2. The apparatus of Claim 1, wherein at least one of the at least substantially reflective surfaces comprises a micro-electro-optic system (MEMS) device
25 operable to undergo a substantially piston-like motion to change its position relative to the input.

06716822-122200

an inner conductive layer disposed inwardly from the
moveable mirror layer and forming a space between the
5 moveable mirror layer and the inner conductive layer;

4. The apparatus of Claim 3, wherein the inner conductive layer comprises a doped semiconductor substrate.

6. The apparatus of Claim 3, wherein the moveable mirror layer comprises a plurality of adjacent mirror strips, at least some of the plurality of adjacent mirror strips separated by air gaps operable to relieve air damping when the mirror strips move relative to the inner conductive layer.

7. The apparatus of Claim 6, wherein all of the moveable mirror strips move at least substantially in unison in response to the voltage difference.

105

8. The apparatus of Claim 7, wherein either the inner conductive layer or each of the moveable mirror strips is coupled to a ground, and wherein the other is operable to receive a control voltage signal.

5

9. The apparatus of Claim 3, wherein a grazing angle between the moveable mirror layer and the signal copy reflected by the moveable mirror layer comprises an angle that is less than forty-five degrees.

10

10. The apparatus of Claim 3, further comprising a second MEMS device disposed between the first MEMS device and the output, the second MEMS device comprising a moveable mirror layer operable to receive a phase shifted signal copy from the first MEMS device and to change its position relative to the first MEMS device to introduce a further phase shift to the signal copy.

15

11. The apparatus of Claim 1, wherein the input comprises a first beam splitter and wherein the output comprises a second beam splitter.

20

12. The apparatus of Claim 1, wherein the input and the output comprise a single beam splitting device.

25

09746822.12200

106

13. The apparatus of Claim 11, further comprising
at least one additional reflective surface between the
beam splitter and the first MEMS device, the at least one
additional reflective surface operable to receive a
5 signal copy from the first beam splitter and to reflect
the signal copy for ultimate reception by the first
mirror.

05746822.122200

107

14. An apparatus operable to facilitate add/drop multiplexing of optical signals, the apparatus comprising:

5 a drop phase shift stage operable to receive an input optical signal and to either drop the input signal or to pass the optical signal toward an output, the drop phase shift stage comprising an at least substantially reflective surface operable to change its position to affect whether the input signal is dropped or passed to
10 the output; and

an add phase shift stage operable to receive and communicate as an output either an added signal or the input signal passed from the drop phase shift stage, the add phase shift stage comprising an at least
15 substantially reflective surface operable to change its position to affect whether the added signal or the input signal is passed to the output.

15. The apparatus of Claim 14, wherein at least one
20 of the at least substantially reflective surfaces comprises a moveable mirror layer of a micro-electro-optic system (MEMS) device operable to undergo a substantially piston-like motion to change its position.

03746632.12200

108

16. The apparatus of Claim 14, wherein the drop phase shift stage comprises:

a beam splitter operable to receive the input signal and communicate at least two copies of the signal in at least two directions; and

a plurality of at least substantially reflective surfaces, each operable to receive one of the signal copies and to reflect the copies for ultimate combination at an output to form an output signal;

wherein at least one of the at least substantially reflective surfaces comprises a moveable mirror layer of a first micro-electro-optic system (MEMS) device, the moveable mirror layer operable to experience a substantially piston-like motion to change its position relative to the beam splitter, the change in position causing a phase shift between the signal copies and a corresponding interference between the signal copies at the output, the input signal being either passed to the add phase shift stage or dropped, depending on the position of the moveable mirror.

09746822-122200

109

17. The apparatus of Claim 14, wherein the add phase shift stage comprises:

a beam splitter operable to receive either the added input signal or the input signal passed from the drop phase shift stage, the beam splitter further operable to communicate at least two copies of the received signal in at least two directions; and

a plurality of at least substantially reflective surfaces, each operable to receive one of the signal copies and to reflect the copies for ultimate combination at an output to form an output signal;

wherein at least one of the at least substantially reflective surfaces comprises a moveable mirror layer of a first micro-electro-optic system (MEMS) device, the moveable mirror layer operable to experience a substantially piston-like motion to change its position relative to the beam splitter, the change in position causing a phase shift between the signal copies to result in the received signal being communicated through the output of the add phase shift stage.

18. The apparatus of Claim 14, wherein the at least substantially reflective surfaces of the add phase shift stage and the drop phase shift stages each comprise a first MEMS-based device having a moveable mirror layer operable to experience a substantially piston-like motion in response to a control signal.

110

19. The apparatus of Claim 18, wherein the first MEMS device comprises:

an inner conductive layer disposed inwardly from the moveable mirror layer and forming a space between the
5 moveable mirror layer and the inner conductive layer;

wherein the moveable mirror layer comprises an at least substantially conductive layer operable to move relative to the inner conductive layer in response to a voltage difference between the moveable mirror layer and
10 the inner conductive layer.

20. The apparatus of Claim 19, wherein the moveable mirror layer comprises a plurality of adjacent mirror strips, at least some of the plurality of adjacent mirror
15 strips separated by air gaps operable to relieve air damping when the mirror strips move relative to the inner conductive layer.

21. The apparatus of Claim 20, wherein all of the
20 moveable mirror strips move at least substantially in unison in response to the voltage difference.

09746822.122200

111

22. A wave division add/drop multiplexer,
comprising:

a wavelength division demultiplexer operable to
separate an optical input signal into a plurality of
5 wavelengths;

an array of optical add/drop multiplexers coupled to
the demultiplexer, at least one of the add/drop
multiplexers comprising:

00745822.1.12200
10 a drop phase shift stage operable to receive an
input wavelength and to either drop the input
wavelength or to pass the input wavelength toward an
output, the drop phase shift stage comprising an at
least substantially reflective surface operable to
change its position to affect whether the input
15 wavelength is dropped or passed to the output; and

an add phase shift stage operable to receive
and communicate as an output either an added
wavelength or the input wavelength passed from the
drop phase shift stage, the add phase shift stage
20 comprising an at least substantially reflective
surface operable to change its position to affect
whether the added wavelength or the input wavelength
is passed to the output; and

a wavelength division multiplexer operable to
25 receive a plurality of output wavelengths from the add
phase shift stage and to multiplex at least some of the
output wavelengths into an optical output signal.

112

23. The wave division add/drop multiplexer of Claim
22, wherein at least one of the at least substantially
reflective surfaces comprises a moveable mirror layer of
a micro-electro-optic system (MEMS) device operable to
5 undergo a substantially piston-like motion to change its
position.

24. The wave division add/drop multiplexer of Claim
22, further comprising a bypass path coupled between the
10 wavelength division demultiplexer and the wavelength
division multiplexer, the bypass path operable to
communicate at least one wavelength directly between the
demultiplexer and the multiplexer without processing the
at least one wavelength.

00746922.122200

113

25. A wave division add/drop multiplexer,
comprising:

a wavelength division demultiplexer operable to
separate an optical input signal into a plurality of
5 wavelengths;

an array of optical add/drop multiplexers coupled to
the demultiplexer, at least one of the add/drop
multiplexers comprising:

an input operable to receive an input
10 wavelength signal and an added wavelength signal,
and to generate a first and a second copy of the
input signal and a first and a second copy of the
added signal;

a plurality of at least substantially
15 reflective surfaces, each operable to receive either
the first signal copies or the second signal copies
and to reflect the copies for ultimate combination
at an output to form an output signal for
transmission, at least one of the at least
20 substantially reflective surfaces comprising a
moveable mirror operable to change its position
relative to the input to create a phase shift
between the first and second signal copies so that
either the input optical signal or the added optical
25 signal is communicated as the output signal
depending on the position of the at least one
moveable mirror; and

a wavelength division multiplexer operable to
receive a plurality of output signals from the array of
30 add/drop multiplexers and to multiplex at least some of
the output wavelengths into an optical output signal.

09745522.1 12/2000

114

26. A wave division add/drop multiplexer,
comprising:

a wavelength division demultiplexer operable to
separate an optical input signal into a plurality of
5 wavelengths;

an array of optical add/drop multiplexers coupled to
the demultiplexer, at least one of the add/drop
multiplexers comprising a micro-electro-optic system
(MEMS) device comprising a moveable mirror layer operable
10 to undergo a substantially piston-like motion to create a
phase difference between a wavelength reflected from the
moveable mirror layer and a substantial copy of that
wavelength, the position of the moveable mirror layer
affecting whether the input wavelength is passed through
15 or dropped from the array; and

a wavelength division multiplexer operable to
receive a plurality of output wavelengths from the array
and to multiplex at least some of the output wavelengths
into an optical output signal.

00746822-122200

115

27. A method of facilitating optical add/drop multiplexing, comprising:

receiving an input optical signal and an added optical signal;

5 generating a first and a second copy of the input signal;

generating a first and a second copy of the added signal;

10 communicating the first signal copies toward a first mirror and the second signal copies toward the second mirror;

changing the position of the first mirror to create a phase shift between the first and second copy when combined at an output; and

15 communicating either an added signal or the input signal as an output signal depending at least in part on the position of the first mirror.

28. The method of Claim 27, wherein the first
20 mirror comprises a micro-electro-optic system (MEMS) device having a moveable mirror layer operable to experience a substantially piston-like motion in response to a control signal.

09746822.120200

29. The method of Claim 28, wherein the MEMS device comprises an inner conductive layer disposed inwardly from the moveable mirror layer and forming a space between the moveable mirror layer and the inner
5 conductive layer; and

wherein changing the position of the moveable mirror layer comprises displacing the moveable mirror layer relative to the inner conductive layer in response to a voltage difference between the moveable mirror layer and
10 the inner conductive layer.

30. The method of Claim 29, wherein the moveable mirror layer comprises a plurality of adjacent mirror strips, at least some of the plurality of adjacent mirror
15 strips separated by air gaps operable to relieve air damping when the mirror strips move relative to the inner conductive layer.

31. The method of Claim 30, wherein changing the
20 position of the moveable mirror layer comprises displacing all of the moveable mirror strips relative to the inner conductive layer substantially in unison in response to the voltage difference.

32. The method of Claim 30, wherein changing the
25 position of the moveable mirror layer comprises:

coupling either the inner conductive layer or each of the moveable mirror strips to a ground; and
applying to the other a control voltage signal.

117

33. The method of Claim 29, wherein changing the
position of the moveable mirror layer comprises
selectively displacing the moveable mirror layer relative
to the inner conductive layer, wherein the distance
5 increases as the voltage difference between the moveable
mirror layer and the inner conductive layer increases.

09746822.122200

receiving an optical input signal at a first stage;
generating a first and a second copy of the input

communicating the first signal copy toward a first mirror and the second signal copy toward the second mirror;

generating a first and a second copy of the signal
received at the second stage;

communicating either the added signal or the input signal from the first stage from the second output depending at least in part on the position of the third mirror.

35. The method of Claim 34, wherein the first mirror comprises a micro-electro-optic system (MEMS) device having a moveable mirror layer operable to experience a substantially piston-like motion in response to a control signal.

119

36. The method of Claim 35, wherein the MEMS device comprises an inner conductive layer disposed inwardly from the moveable mirror layer and forming a space between the moveable mirror layer and the inner
5 conductive layer; and

wherein changing the position of the moveable mirror layer comprises displacing the moveable mirror layer relative to the inner conductive layer in response to a voltage difference between the moveable mirror layer and
10 the inner conductive layer.

37. The method of Claim 36, wherein the moveable mirror layer comprises a plurality of adjacent mirror strips, at least some of the plurality of adjacent mirror
15 strips separated by air gaps operable to relieve air damping when the mirror strips move relative to the inner conductive layer.

38. The method of Claim 37, wherein changing the
20 position of the moveable mirror layer comprises displacing all of the moveable mirror strips relative to the inner conductive layer substantially in unison in response to the voltage difference.

09746822.122200

120

39. A method of facilitating wave division add/drop multiplexing, comprising:

receiving an optical input signal comprising a plurality of wavelengths;

5 separating the optical signal into a plurality of wavelength signals;

communicating at least some of the wavelength signals to an array of optical add/drop multiplexers;

at at least one of the add/drop multiplexers:

10 receiving an input optical signal and an added optical signal;

generating a first and a second copy of the input signal;

15 generating a first and a second copy of the added signal;

communicating the first signal copies toward a first mirror and the second signal copies toward the second mirror;

20 changing the position of the first mirror to create a phase shift between the first and second copy when combined at an output; and

communicating either an added signal or the input signal as an output signal depending at least in part on the position of the first mirror.

06746822-152200

121

40. A method of facilitating wave division add/drop multiplexing, comprising:

receiving an optical input signal comprising a plurality of wavelengths;

5 separating the optical signal into a plurality of wavelength signals;

communicating at least some of the wavelength signals to an array of optical add/drop multiplexers;

at at least one of the add/drop multiplexers:

10 receiving an optical input signal at a first stage;

generating a first and a second copy of the input signal;

15 communicating the first signal copy toward a first mirror and the second signal copy toward the second mirror;

changing the position of the first mirror to create a phase shift between the first and second copy when combined at an output of the first stage;

20 communicating either an added signal or the input signal from the first stage toward a second stage depending at least in part on the position of the first mirror;

25 generating a first and a second copy of the signal received at the second stage;

communicating the first received signal copy toward a third mirror and the second received signal copy toward a fourth mirror;

09745822.122200

122

changing the position of the third mirror to create a phase shift between the first and second received signal copies when combined at the second output; and

- 5 communicating either the added signal or the input signal from the first stage from the second output depending at least in part on the position of the third mirror.

05745822.122200

123

41. An apparatus operable to facilitate add/drop multiplexing of optical signals, the apparatus comprising:

an input operable to receive an input optical signal
5 and an added optical signal, and to generate a first and a second copy of the input signal and a first and a second copy of the added signal;

a plurality of at least substantially reflective surfaces, each operable to receive either the first
10 signal copies or the second signal copies and to reflect the copies for ultimate combination at an output to form an output signal for transmission, at least one of the at least substantially reflective surfaces comprising a Micro-electro-optic system (MEMS) device comprising a
15 plurality of adjacent mirror strips, the mirror strips operable to change their position substantially in unison in a substantially piston-like motion relative to the input to create a phase shift between the first and second signal copies so that either the input optical
20 signal or the added optical signal is communicated as the output signal depending on the position of the at least one moveable mirror.

067468069.01102000

124

42. A method of facilitating optical add/drop multiplexing, comprising:

receiving an input optical signal and an added optical signal;

5 generating a first and a second copy of the input signal;

generating a first and a second copy of the added signal;

communicating the first signal copies toward a first
10 mirror and the second signal copies toward the second mirror, the first mirror comprising a plurality of adjacent mirror strips operable to receive the first signal;

displacing adjacent mirror strips substantially in
15 unison in a substantially piston-like motion to create a phase shift between the first and second copy when combined at an output; and

communicating either an added signal or the input
signal as an output signal depending at least in part on
20 the position of the adjacent mirror strips.

00746821-22991420